

### **Product Data Sheet**

# 0.5% Pt/AT R4751

### DeOxo M

## BASF DeOxo M / R4751 is a uniform grey cylindrical alumina pellet used typically for the catalytic conversion of oxygen or hydrogen (DeOxo reaction)

#### General

R4751 is a catalyst in the form of tablets with nominal dimensions of  $3 \times 3$  mm and with Platinum as the active component. The carefully selected surface area of the carrier allows for high activity and high temperature stability. At the same time, the material shows low pressure drop in gas phase applications due to its size.

#### **Product Application**

R4751 is used to promote the catalytic conversion of hydrogen or oxygen. The reaction can be described by the following chemical formula

 $H_2 + \frac{1}{2} O_2 \rightarrow H_2 O(v) (\Delta_R H) = -242 \text{ kJ/mol} (1)$ 

Applications can be:

- Removal of traces of oxygen from hydrogen
- Removal of traces of oxygen from carbon monoxide or carbon dioxide
- Removal of hydrogen from carbon dioxide by reaction with oxygen (H<sub>2</sub> safety reactor in urea plants)
- Conversion of isotopes of hydrogen

BASF can provide, upon request, technical advice and recommendations on catalyst operating conditions and reactor layout.

An alternative material for these applications can be:

0.5% Pt/AS R4753 (DeOxo MS)

Due to the high exotherm of reaction (1), proper instrumentation and safety measures always need to be put in place to assure full control of the reaction.

Typical reaction temperatures are in the range of ambient up to 200°C / 390 °F depending on the application. The maximum allowable temperature is 500°C / 930°F.

Target Properties	
Chemical Composition (dry basis)	0.5 % wt./wt. Pt on Alumina
Typical Physical Properties	
Packed Bulk Density, kg/l	1.0
Total Surface Area(BET), m <sup>2</sup> /g	90

#### Special Operations

R4751 might gain maximum activity via a short activation procedure. Before unloading, the material should be oxidized.

#### Poisons

R4751 will last for very long times as long as it is not subjected to poisoning by certain impurities. The principal poisons are Sulphur, chlorine compounds, oil, unsaturated hydrocarbons and the vapors of some organic solvents. These materials will deactivate and may eventually poison the catalyst permanently.

#### Storage

R4751 does not deteriorate or constitute any hazard when stored in sealed containers. The containers should not be allowed to become damp or wet and should not be stored in contact with organic or easily oxidizing vapors.

#### Packaging

- 64 I fiber drums with up to 50 kg net

#### **Point of Shipment**

- Rome, Italy

#### About Us

BASF is a leading global manufacturer of catalysts for the chemical industry, with solutions across the chemical value chain. The business comprises chemical catalysts and adsorbents, refinery catalysts and custom catalysts. In the process catalysts business, priority is given to developing new and improved products that enable the chemical industry transformation to netzero emissions.

The division's portfolio also includes battery materials and recycling solutions, as well as environmental catalysts and metal solutions. Customers from a variety of industries including Automotive & Transportation, Chemicals, Plastics or Energy & Resources benefit from our innovative solutions. Further information on BASF's Catalysts division is available on the Internet at www.catalysts.basf.com.

**BASF - We create chemistry** 

#### Americas

BASF Corporation Phone: +1-732-205-5000 Email: catalysts-americas@basf.com

Asia Pacific

BASF (China) Company Limited Phone: +86-21-2039 2549 Email: catalysts-asia@basf.com

**Europe, Middle East, Africa** BASF Services Europe GmbH Phone: +49-30-20055000

Email: catalysts-europe@basf.com

Although all statements and information in this publication are believed to be accurate and reliable, they are presented gratis and for guidance only, and risks and liability for results obtained by use of the products or application of the suggestions described are assumed by the user. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that toxicity data and safety measures are indicated or that other measures may not be required. © 2015 BASF

#### www.catalysts.basf.com/adsorbents

BASF-10715 Rev. 03/22